



## TDK-Lambda

### Caratteristiche del prodotto

- Approvazioni medicali IEC/EN 60601-1 (3rd Edition) & IEC/EN60601-1-11
- Isolamento ingresso - uscita 4kV AC
- Classe II
- Conforme ai requisiti ErP e “DoE efficiency level VI”

### Caratteristiche Principali

- Potenza 40 - 65 W, in base alla tensione di uscita
- Ampia tensione d'ingresso universale 90 ... 264 VAC, Connettore IEC60320-C8
- Modelli singola uscita 5, 12, 15, 19, 24, 28 e 48 V DC
- Cavo di uscita con connettore 4-pin Power-DIN

### Applicazioni tipiche

- Attrezzature ospedaliere, cliniche, dentali e sanitarie
- Monitoraggio
- Imaging
- Applicazioni diagnostiche

### Product Highlights

- Medical approval IEC/EN 60601-1 (3rd Edition) & IEC/EN60601-1-11
- Input - Output Isolation 4kV AC
- Class II
- ErP compliant and meets the “DoE efficiency level VI” requirements

### Key Specifications

- 40 - 65 W, depending on output voltage
- 90...264 VAC Wide universal input voltage, IEC60320-C8 connector
- 5, 12, 15, 19, 24, 28 and 48 V DC Single Output voltage models
- Output Cable terminated with 4-pin Power-DIN connector

### Typical Applications

- Hospital, Dental, Clinical and Healthcare Equipment
- Monitoring
- Imaging
- Diagnostic applications